

10 Using Radeox from other languages	20
10.1 Writing Macros with Groovy	20
10.1.1 Loading Macros with Groovy at runtime	20


```
initialContext.set(
    RenderContext.INPUT_BUNDLE_NAME,
    "myown_markup");
```

Radeox then tries to load the input patterns from *myown_markup.properties*. The name of the output properties file can be set accordingly with

```
initialContext.set(
    RenderContext.OUTPUT_BUNDLE_NAME,
    "myown_markup");
```

Input and output properties may be loaded from different files.

5.4 Natural language locale

Messages for the user which are generated by macros and filters are read from *radeox_messages.properties*. The language locale is set with the default language locale of the JDK but can be overridden with

```
initialContext.set(
    RenderContext.LANGUAGE_LOCALE,
    new Locale("de", "DE"));
```

This forces Radeox to use a German locale. To translate the macros or your own macros to a new language, you should copy *radeox_messages.properties* to e.g. *radeox_messages_de.properties* and then translate the values. The locale looks like

```
#Macros
macro.table.description=Displays a table.
```

The name of the messages bundle file is set with

```
initialContext.set(
    RenderContext.LANGUAGE_BUNDLE_NAME,
    "radeox_messages")
```

Another way is `trtextcomvalGUAG-11.955Td[(own)-292(mac)r18(os)-234(It)NGUAGE_BUNDwhe(ead)`

6 Radeox and PicoContainer

Sometimes it is desired to make the RenderEngine exchangeable. This can be done with a factory pattern. But mo ernrxnflexiernrxn8(ednrxnune)s(ernrxnwith)-3comp.95ntan be


```
public abstract void execute(Writer writer, MacroParameter params)
    throws IllegalArgumentException, IOException;
```

Writer is a java.io.Writer object. To output something from your macro just use

```
writer.write("hello world");
```

If you have to output other objects than Strings then you can encapsulate the writer with java.io.PrintWriter which supports print and println for several

7.1.3


```
public interface Filter {  
    public String filter(String input, FilterContext context);  
  
    public String[] before();  
}
```

```
public boolean isCacheable();
```

7.2.6 Using the locale versions of `RegexTokenFilter` and `RegexReplaceFilter`

Suppose someone does not agree with your former definition of a Smiley and thinks the smiley should look

`:->`

To change the smiley he has to modify your Java code, recompile and de-plot the jar. It's much easier to modify the `radeox_markup_mywiki.properties` file (or the default Radeox properties file)

```
filter.smiley.match=:-\\(filter.smiley.print=:->
```


- A HTML frontend, often with a web framework (WebWork, Struts, Web-


```
33 |     buffer.append(anchor);  
34 |     buffer.append("\>");  
35 |     buffer.append(view);  
36 |
```



```
1 public class GroovyMacroCompile7 {
2   public Macro compileMacro(String macroSource) {
3     Macro macro = null;
4     try {
5       GroovyClassLoade7 gcl = new GroovyClassLoade7();
6       InputStream iscm BT /F34 4.9c{
```